

## MDB-4F

### CENTRAL FILTER SYSTEM WITH FAN

The MDB-4F is a self-cleaning filter unit with integrated extraction fan. It contains four self-cleaning polyester filter cartridges. Pressure controlled automatic cleaning system, resulting in the particulate dropping into a collection container at the bottom of the unit.

The MDB-4F features a frequency inverter.



#### APPLICATIONS

The MDB-4F is intended to be used for the following applications:

- MIG-MAG/GMAW welding
- TIG welding
- FCAW welding
- stick/MMAW welding



Do **not** use the MDB-4F for the following applications or in the following circumstances:

- arc-air gouging
- aluminium laser cutting
- oil mist
- heavy oil mist in welding fume
- extraction of aggressive fumes and gases (e.g. from acids, from alkaline, from soldering paste containing lithium)
- extraction of hot gases (more than 45°C/113°F continuously)
- grinding aluminum and magnesium
- flame spraying
- extraction of cement, saw dust, wood dust etc.
- sucking cigarettes, cigars, oiled tissues and other burning particles, objects and acids
- explosive environments or explosive substances/gases



#### SPECIFICATIONS



##### Physical dimensions and properties

Material (housing)	polyester coated sheet metal
Colour:	
• housing	• black RAL 9005
• cover plates	• yellow RAL 1004
Weight (net) incl. filter cartridges	339 kg (747 lbs)
Fan motor design	IEC
<b>Filter cartridges</b>	
Type	CART-D
Material	polyester fibres
Shape	cylinder
Filter surface area	4 x 15 m <sup>2</sup> (4 x 161.5 ft <sup>2</sup> )
Filter class	• M • MERV 11
<b>Performance</b>	
Fan type	radial (TEV-585)


Working range	1600-3750 m <sup>3</sup> /h (950-2200 CFM)
Available static pressure (after deduction of pressure drop of CART-D and housing)	<ul style="list-style-type: none"> <li>• 1600 Pa at 1600 m<sup>3</sup>/h (6.4 in. WG at 950 CFM)</li> <li>• 1300 Pa at 2500 m<sup>3</sup>/h (5.2 in. WG at 1475 CFM)</li> <li>• 800 Pa at 3500 m<sup>3</sup>/h (3.2 in. WG at 2050 CFM)</li> <li>• 550 Pa at 3750 m<sup>3</sup>/h (2.2 in. WG at 2200 CFM)</li> </ul>
<b>Electrical data</b>	
Power consumption	2,2 kW (3 HP)
Connection voltage:	<ul style="list-style-type: none"> <li>• Europe/USA</li> <li>• Canada</li> </ul>
Default setting:	<ul style="list-style-type: none"> <li>• Europe</li> <li>• USA</li> <li>• Canada</li> </ul>
Nominal current:	<ul style="list-style-type: none"> <li>• Europe</li> <li>• USA</li> <li>• Canada</li> </ul>
Protection class	IP 55 (motor and electronics)
<b>Ambient conditions</b>	
Operating temperature:	<ul style="list-style-type: none"> <li>• min.</li> <li>• nom.</li> <li>• max.</li> </ul>
Max. relative humidity	75%
Outdoor use allowed	yes, if protected against rain
Storage conditions	<ul style="list-style-type: none"> <li>• 5-45°C (41-113°F)</li> <li>• relative humidity max. 75%</li> </ul>
<b>Options and accessories</b>	
SAS-315 straight	duct silencer
SAS-315 elbow 90°	duct silencer
TOL-315	outlet transition from square to round

<b>■ Where used</b>	
Multiple arm systems (max. 3-4 arms in use simultaneously)	
FlexHood systems	
<b>■ Order information</b>	
Article number:	<ul style="list-style-type: none"> <li>• 400-480V/3~/50-60Hz      • 0000100835</li> <li>• 600V/3~/60Hz              • 0000100836</li> </ul>
Number/package	1
<b>■ Shipping data</b>	
Gross weight (incl. pallet)	425 kg (551 lbs)
Packing dimensions (L x W x H)	1800 x 1480 x 2320 mm (70.9 x 58.3 x 91.3 in.)
Harmonized Tariff Code	8421.39.2090
Country of origin	Netherlands

**APPROVALS/CERTIFICATES**





	
	ref. UL-508A

**DIMENSIONS**



	mm	inch		mm	inch
A	2098	82.6	J	606	23.9
B	905	35.6	K	905	35.6
C	896	35.3	L	413	16.3
D	413	16.3	M	Ø 315	Ø 12.4
E	Ø 315	Ø 12.4	N	500	19.7
F	1024	42.3	O	1679	66.1
G	1250	49.2	P	235	9.3
H	1679	66.1	Q	606	23.9
I	135	5.3	R	785	30.9

**FEATURES**

Module with four filter cartridges	
Integrated fan	
Control box incl. frequency inverter	
90 litre hopper design dustbin	

Product type                    **MDB-4F**

Article no.                      *refer to order information*

Product category              central filter systems

Version                            130513/H

Always check the latest version on [www.plymovent.com](http://www.plymovent.com).